



OSW Equipment & Repair, LLC

Quote Number:

3-axle super tri B

Customer: J R Hayes Const

Date: 6/17/2021

Phone:
Payment Contact:
E-Mail:

Salesperson: Brad Sturman
Cell: (206) 818-9534
Bsturman@oswequipment.com
Job #

Quantity	Description	Unit Price	Total
1	2021 OSW DS36SA 43HT » Steel Body on a 3 Axle Trailer w Turntable Installed To Match Following Spec OPTIONS: waste locks \$ 345.00 side boards \$ 368.00 Disc Brakes per axle \$ 1820.00 each asphalt door \$ 893.00 High lift tailgate \$ 4498.00 Late Chassis Delivery Will Delay Build Start Any Modification or Relocation to Frame Components will be Charged Back on a "Time & Material Rate" All OSW Specifications will be STANDARD Build, Unless Stated or NOTED in Received Specification Sheet *Trucks With Low Fuel Will Have a \$250 Additional Charge*	\$	
Customer Signature:		Sub Total:	
Date:		7.8%	
PO#:		F.E.T 12%	
Quote is good for 7 DAYS. 25% Deposit Is Required with Order. Due to the Current Volatility of the Market and the Rising Cost of Materials, Final Price is Subject to Change Without Notice. A Surcharge may be Added to Final Sale Price Prior to Delivery Payment in Full Upon Completion. F.O.B. Woodinville, WA		Quote Total	
		25% Deposit	
		Balance COD	



OSW Equipment & Repair, LLC

OSW 3 AXLE W/1ST AXLE ON TURN TABLE STEEL BOX PONY TRAILER MODEL DS36SA-ST

Trailer Chassis		Initial	
Frame:	1/4" Grade 80 C-Channel Frame & 5/16" Tongue Rails		
Turntable:	26,000 lbs. Capacity; Provides 24 Degrees of Turn Each Way		
Turntable Lock System:	2 - 30/30 Brake Cans Actuated Rods into Reinforced Holes in Turntable Sub-Assembly Holes Only Line Up with Their Respective Rods to Prevent Lock In Any Other Position Except Straight		
Tongue Hinge:	(2) Hinges with Poly Bushings Welded & Gusseted to Both Frame & Tongue Rails		
Tongue:	Air Slide. 3/8" x 8" x 8" Square Tube (STD)(HOUSED REACH LOCKS)		
Tongue Jack:	Top Wind Jack Mounted Roadside on Tongue Rail		
Tongue Eye:	Premier 207L with Poly Bushings		
Hoist:	to Match Body Length		
Rear Hinges:	Heavy Duty 1" Ears & 2" 4140 Pins		
Axles:	(3) - 77.5" Drum 22,500 lbs. (STD)		
ABS:	Haldex 2/S1M Antilock Braking System		
Suspension:	Hutch CH9700 Flange Mount Cast Steel Hangers Front Turn Table Axle: 3 Leaf High Arch Springs Rear Axles: 3 Leaf Low Arch Springs		
Tires:	(6) - 385/65R22.5 Radial		
Wheels:	(6) - 12.25" x 22.5" Non Polished Aluminum Wheels		
Lights	All Lights are LED & Mounted in Rubber Grommets		
Rear Crossmember:	(2) - 4" Lights and (1) License Plate Light in Rear Cross Member. (3) - 2" ICC Cluster Lights Centered Atop the Rear Cross Member.		
Tongue Tube:	(1) - Constant Flashing Light Atop the Tongue Tube		
Add Lights:	NO		
Steps:	(1) - Tongue Rail Step Driver Side		
Flaps:	Mud Flaps Front & Rear of Axles		
Paint:	OSW Black (STD)		

15' 6" Steel Square Trailer Body

Initial

Floor:	3/16" AR450 Steel (STD)		
Sides:	10GA GR50 & 3/16" AR450 Inner Wall (DW)		
Side Height:	39"		
Top Rails:	3/16" AR 450		
Bulkhead:	3/16" AR450 Steel (STD)		
Corrugation:	YES		
Tarp System:	"LC" Electric Tarp - Pull Tarp Brand		
Mount Location:	High		
Tarp Material:	Mesh		
Tarp Color:	N/A		
Integrated Housing:	N/A		
Housing Location:	Top Mount		
Motor Location:	Left Hand (STD)		
Hi Lift:	NO		
Tailgate:	3/16" AR450 Inner Wall & 10 GA Outer (HD DW)		
	<i>Horizontal Channels are Formed Into the Outer Wall - Hinged at Top with 1.25" Pins 90° - Add a Shed Angle to Top of Tailgate</i>		
Haz Locks:	0		
Tailgate Opener:	NO		
Tailgate Locks:	2.5" x 6" Air Operated Cylinder		
Longitudinals	3/16" GR50 Steel 6" (STD)		
Corner Posts:	3/16" GR50 Steel (STD)		
Dog House:	1/4" AR450 Steel (HD)		
Spreader Chains:	(2) 3/8" HD Chains Welded to Underside of Rear Cross Member. Chains Hook to Slotted Brackets on Tailgate		
Side Boards:	Brackets/Pockets ONLY (STD)		
Lights:	ICC/DOT Legal Lights Grommet Mounted LED's		
	(2) 2" Red Marker Per Corner Post (2) Stop, Turn, Tail Light Per Side ABS Light is Forward Facing in Driver Side Corner Post		
Marker Lights:	1 Per Side (2 Total STD)		
Add Lights:	NO		
Backup Camera:	NO		
Mud Flaps:	OSW 30" Heavy Duty Rubber Flaps Mounted on Front & Rear		

